

Water-wash flexo processor series

These proven water-wash flexo processors are selected to deliver optimum performance with Fujifilm's Flenex FW water-washable flexo plates. The series offers a choice of manual or more automated working methods to best suit your production environment.

Key features

- ▶ High quality in-house plate making
- ▶ Reliable operation
- ▶ Robust design
- ▶ Best-in-class waste-water capabilities
- ▶ Unique remote diagnostic service
- ▶ Environmentally friendly system

C-TOUCH

All-in-one clamshell unit

The C-TOUCH features an easy access clamshell design for mounting and washing plates. After being fixed to the stickyplate, the plate rotates orbitally over a fixed set of brushes. Back and forth orbital rotation achieves excellent relief washout which results in clean dot reproduction, also for HD flexo. The all-in-one compact design includes pullout drawers for making exposure steps, light finishing and drying with temperature control.

In combination with Flenex FW plates, the C-TOUCH contributes to the fastest plate-making time in the industry. It is available in three models based on maximum plate size.

System

All-in-one autofeed unit

The System series washout section includes automatic rinsing and pre-drying to reduce plate handling time. The plate is mounted on the stickyplate and excellent relief washout is achieved by the orbital movement of brush heads with the plate moving back and forth. This results in clean dot reproduction, also for HD flexo. The all-in-one design includes pullout drawers for making exposure steps, light finishing and drying with temperature control.

FLENEX FW



System



C-Touch

Specifications

Water-wash flexo processor series	C-Touch 25/30	C-Touch 30/40	C-Touch 36/48	S926B	S927B	S928B
Processor type	Clamshell	Clamshell	Clamshell	Autofeed	Autofeed	Autofeed
Maximum plate size	63 x 76cm	76 x 102cm	92 x 122cm	63 x 86cm	76 x 102cm	92 x 122cm
Plates per hour*	6	6	5	4	4	4
Wash time*	10mins	10mins	12mins	12mins	15mins	15mins
External dimensions (W x L x H)	125 x 152 x 120cm (190 when open)	130 x 198 x 120cm (190 when open)	145 x 220 x 120cm (210 when open)	148 x 270 x 120cm (180 when open)	183 x 335 x 120cm (180 when open)	182 x 335 x 120cm (180 when open)
Weight	505kg	730kg	990kg	1250kg	1450kg	1450kg
Filter dimensions	70 x 45 x 100cm	70 x 45 x 100cm	70 x 45 x 135cm	Intergrated	Intergrated	Intergrated
Filtration weight	45kg	45kg	48kg	-	-	-
Power requirements	400 VAC / 25 A 3 phase	400 VAC / 32 A 3 phase	400 VAC / 40 A 3 phase	400 VAC / 32 A 3 phase	400 VAC / 50 A 3 phase	400 VAC / 50 A 3 phase

*Average productivity. Times vary according to plate parameters.

For further information:

Please contact your local Fujifilm partner.

web www.fujifilm.eu/flex **YouTube** [Fujifilm Print](#) **Twitter** [@FujifilmPrint](#)

Specifications are subject to change without notice. The name FUJIFILM and the FUJIFILM logo are trademarks of FUJIFILM Corporation. All other trademarks shown are trademarks of their respective owners. All rights reserved. E&OE.